

Serial No.: 09/742,745

Attorney's Docket No.:10559/432001/P10502

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (currently amended): A method comprising:
detecting a condition in a processor;
calculating multiple adjustment values for a single register, said calculating of multiple adjustment values occurring concurrently at multiple respective hardware stages within a pipeline of the processor; and

updating [[a]] the single register with one of the adjustment values when an instruction associated with the condition is terminated within the pipeline~~[[;]]~~

~~wherein the stages within the pipeline comprise hardware stages, and data passes between at least two of the stages during a processor cycle.~~

2. (original): The method of claim 1, wherein calculating the adjustment values comprises:

incrementing the adjustment values when the condition is detected; and

decrementing the adjustment values when the instruction leaves the stages.

Serial No.: 09/742,745

Attorney's Docket No.: 10559/432001/P10502

3. (original): The method of claim 1, wherein detecting a condition comprises detecting an access to a specified memory location.

4. (original): The method of claim 1, wherein detecting the condition comprises detecting an instruction within a hardware loop.

5. (original): The method of claim 4, wherein detecting the instruction within the hardware loop comprises detecting a bottom match.

6. (original): The method of claim 1, wherein detecting a condition comprises detecting a watch point.

7. (original): The method of claim 1, wherein updating the register with one of the adjustment values comprises adjusting the register by an amount determined by a counter residing in the stage where the termination occurred.

8. (original): The method of claim 1, wherein updating the register comprises updating a speculative register.

9. (currently amended): An apparatus comprising:

Serial No.: 09/742,745

Attorney's Docket No.: 10559/432001/P10502

a first register;
a second register; and
a set of multiple counters to monitor a difference between the first register and the second register, wherein the first register, second register and set of counters reside in a multi-stage pipeline controlled by a control unit, and the set of counters include a first counter[[s]] maintained at a hardware stage where the first register resides and additional counters maintained at hardware stages after the hardware stage where the first register resides, and

~~wherein the stages of the multi-stage pipeline comprise hardware stages, and data passes between at least two of the stages during a pipeline cycle.~~

10. (currently amended): An apparatus comprising:
a speculative register;
an architectural register; and
a set of multiple counters to monitor a difference between the speculative register and the architectural register, wherein the speculative register, architectural register and set of counters reside in a multi-stage pipeline controlled by a control unit, and the set of counters include a first counter[[s]] maintained at a hardware stage where the speculative register resides and additional counters maintained

Serial No.: 09/742,745

Attorney's Docket No.: 10559/432001/P10502

at hardware stages after the hardware stage where the speculative register resides.

11. (previously presented): The apparatus as in claim 10, wherein the speculative register is a speculative count register and the architectural register is an architectural count register.

12. (cancelled)

13. (previously presented): The apparatus as in claim 9, wherein the set of counters consist of counters residing at stages before an n^{th} stage of a pipeline, and wherein n defines a point at which allowing instructions to flow through the pipeline takes an amount of time less than or equal to a branch penalty.

14. (previously presented): The apparatus as in claim 9, wherein following a termination of an instruction in the pipeline, the control unit is adapted to adjust the first register by an amount determined by a particular counter maintained in a stage where the termination occurred.

Serial No.: 09/742,745

Attorney's Docket No.:10559/432001/P10502

15. (previously presented): The apparatus as in claim 9, wherein the control unit is adapted to:

increment the counters when the first register is adjusted because of a detected condition; and

decrement a respective counter when an instruction associated with the condition leaves a respective stage associated with the respective counter.

16. (currently amended): A system comprising:

a static random access memory device;

a first register;

a second register;

a set of multiple counters; and

a processor coupled to the static random access memory device, wherein the processor includes an execution pipeline and a control unit adapted to:

increment the counters when the first register is adjusted because of a detected condition; and

decrement a respective counter when an instruction associated with the condition leaves a respective hardware stage of the pipeline associated with the respective counter, each of the counters being maintained at a separate respective hardware stage

Serial No.: 09/742,745

Attorney's Docket No.: 10559/432001/P10502

~~wherein the counters are maintained for corresponding hardware stages of the execution pipeline, and data passes between at least two of the hardware stages during a system cycle.~~

17. (original): The system of claim 16, wherein following a termination of the pipeline, the control unit is adapted to adjust the first register.

18. (previously presented): The system of claim 17, wherein the control unit is adapted to adjust the first register by an amount determined by one of the set of counters.

19. (original): The system of claim 18, wherein the one of the set of counters is a particular counter residing in a stage of the pipeline where the termination occurred.

20. (original): The system of claim 17, wherein the control unit is adapted to drain unaborted instructions and write the first register with the data in the second register, if the termination occurs in a stage of the pipeline after an n^{th} stage.